


MIMOSA 12

Rivestimento in acciaio verniciato e top in ghisa.

Painted steel lining and cast-iron top.
Verkleidung aus lackiertem Stahl und Oberteil aus Gusseisen.

Habillage en acier peint et couvercle en fonte.

Revestimiento de acero pintado y parte superior de fundición.



11,48 kw Potenza termica globale Global heat output Gesamtwärmeleistung Puissance thermique globale Potencia térmica global	10,40 kw Potenza termica nominale Nominal heat output Nennwärmeleistung Puissance thermique nominale Potencia térmica nominal	96,57 % Rendimento fino a Efficiency up to Wirkungsgrad bis Rendement jusqu'à Rendimiento hasta	240 m³ Volume riscaldabile Maximum heated space Raumheizvermögen Volume de chauffe Volumen a calentar
20 Kg Capacità serbatoio Hopper capacity Inhalt Pelletbehälter Capacité du réservoir Capacidad del depósito	min 0,8 - max 2,0 Kg/h Consumo pellet Pellet consumption Pelletverbrauch Consommation de granulés Consumo de pellets	30 h Autonomia max Max. operating time Max. Betriebsdauer ohne Nachfüllen Autonomie maxi Autonomía máx.	Ø 80 mm Dimensioni tubo scarico fumi Flue size Rauchrohrdurchmesser Tube d'évacuation des fumées Dimensiones del tubo de salida de humos
Ø 40 mm Dimensioni ingresso aria Air intake size Durchmesser Lufteintritt Dimensions prise d'air Dimensiones entrada aire	50/300 watt Assorbimento elettrico Power consumption Stromaufnahme Puissance électrique absorbée Absorción eléctrica	L 56 x P 54 x H 102 cm Dimensioni stufa Stove dimensions Ofenmaße Dimensions du poêle Dimensiones de la estufa	L 65 x P 60 x H 125 cm Dimensioni imballo Packaging dimensions Verpackungsgröße Dimensions emballage Dimensiones del embalaje



Bianco - White - Weiß
Blanc - Blanco



Bordeaux - Burgundy
Bordeaux - Bordeaux - Burdeos

